



- NOTES:
1. ALL DIMENSIONS ARE IN MILLIMETERS
 2. GLASS THICKNESS: 1/12mm NOMINAL
 3. TOUCHSCREEN ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING
 4. CABLE ROUTING ADDS A MAXIMUM OF 0.2/2.5mm TO INDICATED GLASS DIMENSIONS
 5. CONNECTOR MATES WITH ANY OF THE FOLLOWING:
- DV300S/U, DV400U, GT4001S/U, 2701RSU.
 6. TRANSDUCERS ARE LOCATED AT THE POSITIONS WHERE THE GLASS IS BEVELED.

Part #.	Glass Thickness	Surface	AV Option
DV15L6	6mm	Flat	HS/TS/T

CONNECTOR	
PIN	SIGNAL
1	GROUND
2	KEY
3	Y RECEIVE(+)
4	Y TRANSMIT(+)
5	Y RECEIVE(-)
6	Y TRANSMIT(-)
7	GROUND
8	X TRANSMIT(-)
9	X RECEIVE(-)
10	X TRANSMIT(+)
11	X RECEIVE(+)
12	KEY

DV15L6
 Digital Vision Ltd.
 DATE: 06/05/05